LIGHT SOURCES

2773:

5W-75W LAMPS ONLY: 120V Incandescent or LED

2774:

5W-50W LAMPS ONLY: 120V Incandescent or LED Compatible

OPTICS

ADJUSTABLE/HORIZONTAL

AIMING: Up to 90° tilt from vertical axis and up to 355° rotation around vertical axis.

DESIGN:

Unique Integral Construction FINISH/COLORS: Anodized (Clear) PRODUCTION PROCESS:

CNC Precision-Spun

MATERIAL: Specification-Grade Aluminum Alloy, .060" Thick

CONSTRUCTION

HOUSING:

Die-Formed Fabrication

FINISH/COLORS:

- Powdercoat Paint Colors (2)
 - Black (BK)
 - White (WH)

DIMENSIONS:

- 2773: 9¾" H x 4½" Dia.
- 2774: 8¾" H x 4" Dia.

INSTALLATION

MOUNTING:

- Mounts to 120V AC QuantaLight Track Systems
 - TSQ1:
 - 1-Circuit/1-Neutral (1C1N)
 - TSQ2:
 - 2-Circuit/1-Neutral (2C1N)
- Mounts to 1-Circuit or 2-Circuit Track System Platforms

ADAPTERS: Listed Components

DIMMING

INPUT VOLTAGE: 120V at 50/60 Hz (System Adapter Dependant)

DIMMING: TRIAC/ELV 5% dimmable on the input primary, line-side circuit of the track system. Consult dimmer manufacturer for compatibility and conditions of use.

COMPLIANCES/WARRANTY

cETLus LISTED RoHS COMPLIANT LED COMPATIBLE DRY LOCATIONS ONLY 2773/2774

INCANDESCENT/LED TRACK HEADS

2773



(П). жонз

☑2773

MODEL TRACK ADAPTER **☑Q2** 1C1N & 2C1N (120V)

FINISH

TRACK HEAD

□5 Black (Painted)

□6 White (Painted)

TRACK HEAD MODEL TRACK ADAPTER

☑2774

☑Q2 1C1N & 2C1N (120V)

FINISH

□5 Black (Painted) □6 White (Painted) 2774



