

### 2781

#### LED LIGHT ENGINE

##### WATTS/LUMENS:

- **2781:** 17W/1200 lm
- **2782:** 13W/800 lm
- **2783:** 8W/520 lm

##### CR/CCT:

80/3000K

##### BINNING:

3 SDCM

##### THERMAL MANAGEMENT:

Passive  
**LIFE (RATED):**  
 50,000 hours based on LED testing per LM80-08 and projected values from IESNA TM21-11.

##### LED:

- **2781:** PAR38 LED Lamp (17 Watts Max) Included
- **2782:** PAR30 LED Lamp (13 Watts Max) Included
- **2783:** PAR20 LED Lamp (8 Watts Max) Included

##### BASE:

- Medium Base (E26)
- Replaceable PAR LED Light Engine
  - **2781:** PAR38 (17W Max)
  - **2782:** PAR30 (13W Max)
  - **2783:** PAR20 (8W Max)

#### OPTICS

**BEAM ANGLES:** 40°

##### ADJUSTABLE/HORIZONTAL

**AIMING:** Up to 90° tilt from vertical axis and up to 355° rotation around vertical axis.

##### DESIGN:

Unique Integral Construction

**FINISH/COLORS:** Anodized (Clear)

##### PRODUCTION PROCESS:

CNC Precision-Spun

**MATERIAL:** Specification-Grade Aluminum Alloy, .060" Thick

#### CONSTRUCTION

##### HOUSING:

Die-Formed Fabrication

##### FINISH/COLORS:

- Powdercoat Paint Colors (3)
  - Black (BK)
  - White (WH)
  - Silver Gray (SL)

##### DIMENSIONS:

- **2781:** 9½" H x 5" Dia. (Large Gimbal Ring)
- **2782:** 8" H x 4¼" Dia. (Medium Gimbal Ring)
- **2783:** 6¾" H x 3½" Dia. (Small Gimbal Ring)

#### INSTALLATION

##### MOUNTING:

- Mounts to 120V AC *QuantaLight* Track Systems
  - TSQ1: 1-Circuit/1-Neutral (1C1N)
  - TSQ2: 2-Circuit/1-Neutral (2C1N)
- Mounts to 1-Circuit or 2-Circuit Track System Platforms

**ADAPTERS:** Listed Components

#### DIMMING

**INPUT VOLTAGE:** 120V at 50/60 Hz (System Adapter Dependant)

**DIMMING:** TRIAC/ELV 5% dimmable on the input primary, line-side circuit of the track system. Consult dimmer manufacturer for compatibility and conditions of use.

#### COMPLIANCES/WARRANTY

**cETLus LISTED**  
**ENERGY STAR (CONSULT FACTORY)**

**FCC COMPLIANT**  
**5-YEAR LIMITED WARRANTY**

**RoHS COMPLIANT**  
**ENERGY-EFFICIENT**

**LED**  
**DRY LOCATIONS ONLY**

<b>TRACK HEAD MODEL</b>	<input checked="" type="checkbox"/> <b>2781</b>
<b>TRACK ADAPTER</b>	<input checked="" type="checkbox"/> <b>Q2 1C1N &amp; 2C1N (120V)</b>
<b>CCT</b>	<input checked="" type="checkbox"/> <b>30 3000K</b>
<b>LUMENS</b>	<input checked="" type="checkbox"/> <b>12 1200 lm</b>
<b>OPTICS</b>	<input checked="" type="checkbox"/> <b>40 40°</b>
<b>FINISH</b>	<input type="checkbox"/> <b>5 Black (Painted)</b> <input type="checkbox"/> <b>6 White (Painted)</b> <input type="checkbox"/> <b>20 Silver Gray (Painted)</b>



*\*Also Available in Black or Silver Gray*

					<b>1C1N</b>
<b>2C1N</b>	<b>DRY ONLY</b>				

### 2782

<b>TRACK HEAD MODEL</b>	<input checked="" type="checkbox"/> <b>2782</b>
<b>TRACK ADAPTER</b>	<input checked="" type="checkbox"/> <b>Q2 1C1N &amp; 2C1N (120V)</b>
<b>CCT</b>	<input checked="" type="checkbox"/> <b>30 3000K</b>
<b>LUMENS</b>	<input checked="" type="checkbox"/> <b>08 800 lm</b>
<b>OPTICS</b>	<input checked="" type="checkbox"/> <b>40 40°</b>
<b>FINISH</b>	<input type="checkbox"/> <b>5 Black (Painted)</b> <input type="checkbox"/> <b>6 White (Painted)</b> <input type="checkbox"/> <b>20 Silver Gray (Painted)</b>



*\*Also Available in Black or Silver Gray*

					<b>1C1N</b>
<b>2C1N</b>	<b>DRY ONLY</b>				

# 2783

## LED TRACK HEADS

# 2783

### LED LIGHT ENGINE

#### WATTS/LUMENS:

- **2781:** 17W/1200 lm
- **2782:** 13W/800 lm
- **2783:** 8W/520 lm

#### CRI/CCT:

80/3000K

#### BINNING:

3 SDCM

#### THERMAL MANAGEMENT:

Passive  
LIFE (RATED):  
50,000 hours based on LED testing per LM80-08 and projected values from IESNA TM21-11.

#### LED:

- **2781:** PAR38 LED Lamp (17 Watts Max) Included
- **2782:** PAR30 LED Lamp (13 Watts Max) Included
- **2783:** PAR20 LED Lamp (8 Watts Max) Included

#### BASE:

- Medium Base (E26)
- Replaceable PAR LED Light Engine
  - **2781:** PAR38 (17W Max)
  - **2782:** PAR30 (13W Max)
  - **2783:** PAR20 (8W Max)

### OPTICS

#### BEAM ANGLES:

40°

#### ADJUSTABLE/HORIZONTAL

AIMING: Up to 90° tilt from vertical axis and up to 355° rotation around vertical axis.

#### DESIGN:

Unique Integral Construction

#### FINISH/COLORS:

Anodized (Clear)

#### PRODUCTION PROCESS:

CNC Precision-Spun  
ALUMINUM ALLOY, .060" THICK

### CONSTRUCTION

#### HOUSING:

Die-Formed Fabrication

#### FINISH/COLORS:

- Powdercoat Paint Colors (3)
  - Black (BK)
  - White (WH)
  - Silver Gray (SL)

#### DIMENSIONS:

- **2781:** 9½" H x 5" Dia. (Large Gimbal Ring)
- **2782:** 8" H x 4¼" Dia. (Medium Gimbal Ring)
- **2783:** 6¾" H x 3½" Dia. (Small Gimbal Ring)

### INSTALLATION

#### MOUNTING:

- Mounts to 120V AC *QuantaLight* Track Systems
  - TSQ1: 1-Circuit/1-Neutral (1C1N)
  - TSQ2: 2-Circuit/1-Neutral (2C1N)
- Mounts to 1-Circuit or 2-Circuit Track System Platforms

#### ADAPTERS:

Listed Components

### DIMMING

INPUT VOLTAGE: 120V at 50/60 Hz (System Adapter Dependant)

DIMMING: TRIAC/ELV 5% dimmable on the input primary, line-side circuit of the track system. Consult dimmer manufacturer for compatibility and conditions of use.

### COMPLIANCES/WARRANTY

- cETLus LISTED
- ENERGY STAR (CONSULT FACTORY)
- FCC COMPLIANT
- 5-YEAR LIMITED WARRANTY
- RoHS COMPLIANT
- ENERGY-EFFICIENT
- LED
- DRY LOCATIONS ONLY

TRACK HEAD MODEL	<input checked="" type="checkbox"/> 2783
TRACK ADAPTER	<input checked="" type="checkbox"/> Q2 1C1N & 2C1N (120V)
CCT	<input checked="" type="checkbox"/> 30 3000K
LUMENS	<input checked="" type="checkbox"/> 05 520 lm
OPTICS	<input checked="" type="checkbox"/> 40 40°
FINISH	<input type="checkbox"/> 5 Black (Painted) <input type="checkbox"/> 6 White (Painted) <input type="checkbox"/> 20 Silver Gray (Painted)



*\*Also Available in Black or Silver Gray*

QWICK COMMERCIAL | TRACK | TRACK LUMINAIRES | TRACK HEADS | LED | 2871 Series (Continued)