OuantaLight	6025	
SPECIFICATION SHEET	BAFFLE/TRIM	
FEATURES 6 10 10		
DESIGN: Self-Flanged, Two-Piece Construction FINISH/COLORS/TRIM:		
Painted (Black or White) or Anodized (Clear,	Catalog #:	
Haze, or Wheat); Painted White Flange Trim PRODUCTION PROCESS: CNC Precision-Spun	Туре:	
MATERIAL: Specification-Grade Aluminum	Project:	
Alloy, .060" Thick LENS COVER: Clear Glass	Prepared By:	
COMPATIBILITY		
RECESSED DOWNLIGHTS:	AT A GLANCE	
RL4A SeriesRL4V Series	Symmetrical output, baffle	Ы
RL4VR Series	downlight style trim series for	
COMPLIANCES/WARRANTY	the RL4, 4" diameter recesse	
5-YEAR LIMITED WARRANTY	downlights. The trims are availab	
SUITABLE FOR DAMP LOCATIONS LED	in round aperture	
• BAFFLE/TRIM	as well as an assortment of colo	
	and finishes. Made from die-ca	
	aluminum, the trims can be painted or anodized to meet the needs	
	the most difficult of application	
	The trims are configured for	
	flanged installations.	

ORDER CONFIGURATOR

To order, select one option from each table column to configure the desired baffle/trim product catalog code. Then, fill in the boxes below (e.g., Baffle/Trim #: 6025-R-WH-SW). To order recessed downlights, use the corresponding specification sheet(s) for the desired compatible recessed downlight series.



