\bigcirc	uantaL	ight [™]
	SPECIFICATION	SHEET

604

DOWNLIGHT/TRIN

FEATURES (SYLAR) (S) LED

Downlight/trim 💷

DESIGN: Self-Flanged, Two-Piece Construction FINISH/COLORS/TRIM:

Painted (Black or White) or Anodized (Clear, Haze, or Wheat); Painted White Flange Trim

PRODUCTION PROCESS: CNC Precision-Spun

MATERIAL: Specification-Grade Aluminum Alloy, .060" Thick

LENS COVER: Clear Glass

COMPATIBILITY

RECESSED DOWNLIGHTS:

- RL6A Series
- RL6V Series
- RL6VR Series

COMPLIANCES/WARRANTY

- 🐑 5-YEAR LIMITED WARRANTY
- SUITABLE FOR DAMP LOCATIONS
- LED LED
- DOWNLIGHT/TRIM

Catalog #: Type:

Project:

Prepared By:

AT A GLANCE

Symmetrical output, downlight style trim series for the RL6, 6" diameter recessed downlights. The trims are available in either round or square apertures as well as an assortment of colors and finishes. Made from die-cast aluminum, the trims can be painted or anodized to meet the needs of the most difficult of applications. The trims are configured for flanged installations.

ORDER CONFIGURATOR

To order, select one option from each table column to configure the desired downlight/trim product catalog code. Then, fill in the boxes below (e.g., Downlight/Trim #: 6041-R-WH-SW). To order recessed downlights, use the corresponding specification sheet(s) for the desired compatible recessed downlight series.

