

6043

ECIFICATION SHEET WET LOCATION/SHOWER TRIN

FEATURES



SHOWER

DESIGN:

Self-Flanged, Two-Piece Construction

FINISH/COLORS/TRIM:

Painted (White); Painted White Flange Trim

PRODUCTION PROCESS:

CNC Precision-Spun

MATERIAL: Specification-Grade Aluminum

Alloy, .060" Thick

LENS COVER: Sealed and Frosted Glass

COMPATIBILITY

RECESSED DOWNLIGHTS:

- RL6A Series
- RL6V Series
- RL6VR Series

COMPLIANCES/WARRANTY

(S)

5-YEAR LIMITED WARRANTY

இ SUITABLE FOR WET LOCATIONS

♥ SHOWER TRIM

NOTES:

The internal reflector (located behind the frosted glass) comes in white only. Combined with the frosted glass, a white reflector helps provide smooth light output.

The ceiling cutout should be 6 3/4" inches. Any larger will risk the hole being visible.

Damp and wet location rating does not mean water proof. Only mount downlight fixtures in cavity protected from water intrusion. Not for use in car wash or simlar applications where the exposed trim will be sprayed with force. If used outdoors, seal the trim piece with latex sealant to block insect intrusion. If insects can get into ceiling cavity, use a Type IC downlight fixture.



Catalog #:

Type:

Project:


Prepared By:

AT A GLANCE

Shower compliant, downlight style trim series for the RL6, 6" diameter recessed downlights. The trims are available in either round or square apertures in a White finish. Made from die-cast aluminum, the trims can be painted or anodized to meet the needs of the most difficult of applications. The trims are configured for flanged installations.

ORDER CONFIGURATOR

To order, select one option from each table column to configure the desired shower/trim product catalog code. Then, fill in the boxes below (e.g., Shower/Trim #: 6043-S-WH-SW). To order recessed downlights, use the corresponding specification sheet(s) for the desired compatible recessed downlight series.



QUICK VIEW

