



FEATURES



LED LIGHT ENGINE

WATTS/LUMENS:

14W / 850 lm

CRI/CCT:

90/3000K

THERMAL MANAGEMENT: Passive

LIFE(RATED): 50,000 hours based on LED testing per LM80-08 and projected values from IESNA TM21-11

LED DRIVER

OUTPUT POWER SUPPLY:

AC LED Engine

INPUT VOLTAGE:

120V at 50/60 Hz

DIMMING:

- TRIAC/ELV, 10% (120V AC Only)

COMPLIANCES/WARRANTY

cETLus LISTED

FCC COMPLIANT

5-YEAR LIMITED WARRANTY

ENERGY-EFFICIENT

LED

INSTALLATION

CEILING or WALL:

- Surface Mounted
- Ceiling or Wall
- Indoors Only

MOUNTING:

- J-Box Mounted

DIMENSIONS

8" Diameter x 1" High

OPTICS

Frosted plastic lens

ENCLOSURE COLORS

White, Brushed Nickel, or Antique Bronze
(i.e. almost black grey-brown)

Catalog #:

Type:

Project:

Prepared By:

AT A GLANCE

8" Diameter low-profile, surface mounted, ceiling luminaire. Edge-lit LED and frosted lens ensures smooth, even light distribution with no hot spots on lens. Cast aluminum body and trim gives this luminaire a sturdy and long lasting quality that outlasts other lesser products.

RECESSED DOWNLIGHT #

7052	
SIGN MODEL	Frame Color

7052

-6 White

-33 Brushed Nickel

-79 Antique Bronze

QUICK VIEW

