84 Series

8401

APPLICATIONS

REMODEL for COMMERCIAL or RESIDENTIAL:

8401

LIGHT SOURCES LED/INCANDESCENT COMPATIBILITY:

- LED (50 Watts Max)
- Incandescent (50 Watts Max) . Lamps Sold Separately (Refer to Compatible Trims for Compatible Lamp Types and Sizes)

EDISON BASE LAMPHOLDER: Medium Base (E26)

THERMAL MANAGEMENT: Passive ADJUSTABLE SOCKET CUP:

Socket cup adjusts vertically.

COMPATIBLE TRIMS

FINISH/COLORS/TRIM: See Compatible Trims on Website

INSTALLATION

CEILING:

- Accommodates Up to 1" Thickness
- 41/8" Ceiling Cutout Size
- Box Type:

Non-Type IC:

Insulation to Be Kept 3" Away Non Air-Tight

MOUNTING:

Spring Clips Allow for Fast and Easy Installation

BOX WIRING:

RESIDENTIAL | RECESSED DOWNLIGHTS | 4" Diameter | 84 Series


Integral Thru-Branch, 2 In/2 Out


COMPLIANCES/WARRANTY

. % cULus LISTED

SUITABLE FOR DAMP LOCATIONS

- LED LED COMPATIBLE
- Ö RECESSED DOWNLIGHT








NC

4" DIAMETER INCANDESCENT/LED RECESSED REMODEL

RIM

c(UL) us




84 SERIES TRIMS (See more trim options on pages 124 & 125.)

Gimbal Ring Outside Diamet 50W PAR20

5"

1 3/4"

t





3407-6 Whi Gimbal Ring 5" Outside Diameter 50W PAR20

1


QuantaLight


5"

Brushed Nickel Gimbal Ring Outside Diamet 50W PAR20

5










Metal Baffle 5" Outside Diameter 55W PAR16 50W PAR20/R20 40W A19

Metal Baffle 5" Outside Diame 55W PAR16 50W PAR20/R20 . amete 40W A19



DESIGN COPYRIGHT ©