APPLICATIONS

NEW CONSTRUCTION for COMMERCIAL OR RESIDENTIAL:

8413

LIGHT SOURCES LED/INCANDESCENT

- COMPATIBILITY:
- LED (50 Watts Max)
- Incandescent (50 Watts Max) Lamps Sold Separately (Refer to Compatible Trims for Compatible Lamp Types and Sizes)

EDISON BASE LAMPHOLDER: Medium Base (E26)

THERMAL MANAGEMENT: Passive ADJUSTABLE SOCKET CUP:

Socket cup adjusts vertically.

COMPATIBLE TRIMS

FINISH/COLORS/TRIM:

See Compatible Trims on Website

INSTALLATION

- CEILING:
- Accommodates Up to 1" Thickness
- 41/8" Ceiling Cutout Size

Box Type:

- Type IC: Suitable for Direct
- Contact with Insulation
- Air-Tight
- MOUNTING:
- Adjustable Hanger Bars (14" to 24")

BOX WIRING:

Integral Thru-Branch, 4 In/4 Out

COMPLIANCES/WARRANTY


- cULus LISTED SUITABLE FOR DAMP LOCATIONS
- LED LED COMPATIBLE
- Ø. RECESSED DOWNLIGHT

84 Series (Cont 4" DIAMETER INCANDESCENT/LED RECESSED DOWNLIGHT

8413



84 SERIES TRIMS (See more trim options on pages 124 & 125.)



8407-6 White

5'

5"

Gimbal Ring Outside Diameter 50W PAR20

1

8405-6 White Baffle 8405-5 Black Baffle Wall Wash 5" Outside Diameter 50W PAR20/R20 Wall Wash 5" Outside Diameter 50W PAR20/R20 40W A19 40W A19

8407-33

Brushed Nickel Gimbal Ring Outside Diamet

50W PAR20

5



8407-5 Black

Gimbal Ring Outside Diamet 50W PAR20

5'

1 3/4"


t


JuantaLight



40W A19

40W A19







8430-5 Black Metal Baffle 5" Outside Diameter 55W PAR16 50W PAR20/R20 Metal Baffle 5" Outside Diameter 55W PAR16 50W PAR20/R20 40W A19

