

### FEATURES



### LED LIGHT ENGINE

**INTEGRATED LED: 1**

**WATTS/LUMENS:** 10W/650 lm

**CRI:** 90

**POWER FACTOR (Pf):** >.95

**THD:** <10%

**INPUT VOLTAGE:** 120V at 50/60 Hz

**STARTING TEMPERATURE:** -20°C - 80°C

**DIMMING:** 10% of Output

### EDISON ADAPTER:

Medium Base (E26) with Connector

(Compatible with Incandescent Downlights)

### CONSTRUCTION

#### MAIN MATERIAL:

All Die-Cast Aluminum Construction  
(Housing and Trim)

**OTHER MATERIAL:** Sealed White Frosted  
Acrylic Lens Cover and Brushed Nickel  
Round Flanged Trim

**FINISH:** Powder-Coat Polyester (Painted)

**FLANGE SIZE:** .75

### INSTALLATION

#### CEILING:

- Accommodates Up to 1 1/4" Thickness

#### MOUNTING:

- Dual-Torsion Spring Mounting Assemblies
- Integral Mounting Springs
- Wet Rated

### COMPLIANCES/WARRANTY

**cETLus LISTED**

**FCC COMPLIANT**

**5-YEAR LIMITED WARRANTY**

**RoHS COMPLIANT**

**SUITABLE FOR WET LOCATIONS**

**LED**

**RECESSED DOWNLIGHT**



Catalog #:

Type:

Project:

Prepared By:

### AT A GLANCE

- Sturdy, Exquisite Construction
- 5-Year Limited Warranty on Integrated LED
- Sealed White Frosted Acrylic Lens Cover
- Suitable for Indoor or Outdoor
- Extreme Durability and Top Quality Protection
- Available In A Variety Of Finishes
- Outer Lacquer Finish Provides Attractive Sheen and Additional Protection Layer
- High-Quality, Corrosion-Resistant, and Rust-Resistant All-Aluminum (Housing and Trim)
- Go Green—Environmentally Friendly, Energy-Efficient Integrated LED
- Compact Light Fits Easily in Small Spaces
- 650 Lumens
- 3000K Color Temperature
- 90 CRI
- Dimmable (10% of Output)
- Conveniently Suitable for Wet Locations
- Features Ability to Start Up in Cold Weather (Operates From -20°C to 80°C)
- Heat-Resistant Components Withstand Up to 10W
- 1-Light Fixture (Integrated LED Included)
- FREE Medium Base (E26) Adapter Included
- Compatible with Non-Type IC (Insulation Must Be Kept 3" Away) or Type IC (Suitable for Direct Contact with Insulation) 4" or 3" Recessed Downlights
- Individually Inspected for Quality Assurance
- cULus Listed for Safety

### ORDER CONFIGURATOR

To order, select one option from each table column to configure the desired retrofit downlight product catalog code. Then, fill in the boxes below (e.g., Retrofit Downlight #: 8417-33).

### RETROFIT DOWNLIGHT #

8417	-	
MODEL	FINISH	
<input checked="" type="checkbox"/> 8417	<input type="checkbox"/> -6 ( White) <input type="checkbox"/> -33 (Brushed Nickel) <input type="checkbox"/> -79 ( Antique Bronze)	