

LED LIGHT ENGINE

WATTS/LUMENS:

- 8650 or 8654: 13W/950 lm

CR/CCT:

- 8650: 90/3000K
- 8654: 90/4000K

POWER FACTOR (Pf): >.95

INPUT VOLTAGE: 120V at 50/60 Hz

STARTING TEMPERATURE:

⊖ -20°C

OPERATING TEMPERATURE:

⊖ <80°C

DIMMING: 10% of Output

EDISON ADAPTER: Medium Base

(E26) with Connector (Compatible with Incandescent Downlights)

LENS COVER: Sealed and Frosted

MATERIAL: All-Aluminum Construction (Housing and Trim)

LIFE (RATED):

50,000 hours based on LED testing per LM80-08 and projected values from IESNA TM21-11.

CONSTRUCTION

FINISH:

- White (Painted)
- Brushed Nickel
- Antique Bronze

INSTALLATION

CEILING:

- Type IC or Non-Type IC
 - Type IC Suitable for Direct Contact with Insulation
 - Non-Type IC Insulation to Be Kept 3" Away

MOUNTING:

- Dual-Torsion Spring Mounting Assemblies
- Integral Mounting Springs

SUITABLE FOR INDOOR OR OUTDOOR USE

COMPLIANCES/WARRANTY

 cULus LISTED

 5-YEAR LIMITED WARRANTY

 SUITABLE FOR WET LOCATIONS

 ENERGY-EFFICIENT

 LED

 RECESSED DOWNLIGHT

RETROFIT DOWNLIGHT MODEL

- 8650 (3000K, 13W/950lm)
- 8654 (4000K, 13W/950lm)

FINISH

- 6 White (Painted)
- 33 Brushed Nickel
- 79 Antique Bronze



