



LED LIGHT ENGINE

WATTS/LUMENS:
30W/2000 lm (One 15W/1000 lm Uplight and One 15W/1000 lm Downlight)
CRI: 80
CCT: 3000K
BINNING: 3 SDCM
THERMAL MANAGEMENT: Passive
LIFE (RATED): 50,000 hours based on LED testing per LM80-08 and projected values from IESNA TM21-11.

COMPLIANCES/WARRANTY

cULus LISTED
FCC COMPLIANT
2-YEAR LIMITED WARRANTY
RoHS COMPLIANT
SUITABLE FOR WET LOCATIONS
ENERGY-EFFICIENT
LED
UPLIGHT/DOWNLIGHT CYLINDER

LED DRIVER

OUTPUT POWER SUPPLY: Class II
POWER FACTOR (Pf): >.9
THD: <20%
INPUT VOLTAGE: 120V at 50/60 Hz
DIMMING:
* TRIAC/ELV, 5% (120V AC Only)

CONSTRUCTION

HOUSING: Formed & Welded All-Aluminum
FINISH:

- Powdercoat Paint Colors (4)
 - Black (BK)
 - White (WH)
 - Antique Bronze (AB)
 - Silver Gray (SL)

INSTALLATION

SIZE: 5" Dia. x 14" H x 7¾" E
MOUNTING: Surface wall mounting only.
Mounting canopy assembly secures luminaire to wall-mounted junction box.

Catalog #:

Type:

Project:

Prepared By:

AT A GLANCE

Fixed-position downlight cylinder incorporating state-of-the-art LED technology. Aperture 5". Offered as a surface wall mount fixture. Uplight and downlight configuration.

ORDER CONFIGURATOR

To order, select one option from each table column to configure the desired cylinder product catalog code. Then, fill in the boxes below (e.g., Cylinder #: CL504-30-20-LELV-AB-1).

CYLINDER #					
CYLINDER MODEL	CCT	LUMENS	DIMMING	FINISH	VOLTAGE
<input checked="" type="checkbox"/> CL504	<input checked="" type="checkbox"/> 30 3000K	<input checked="" type="checkbox"/> 20 2000 lm	<input checked="" type="checkbox"/> LELV Flicker-Free TRIAC/ELV, 5% (120V Only)	<input type="checkbox"/> BK Black (Painted) <input type="checkbox"/> WH White (Painted) <input type="checkbox"/> AB Antique Bronze (Painted) <input type="checkbox"/> SL Silver Gray (Painted)	<input checked="" type="checkbox"/> 1 120V

QUICK VIEW

Surface Wall Mount
E: 7¾"

