



## LED LIGHT ENGINE

**WATTS/LUMENS:** 15W/1000 lm

**CRI/CCT:** 80/3000K

**BINNING:** 3 SDCM

**THERMAL MANAGEMENT:** Passive

**LIFE (RATED):** 50,000 hours based on LED testing per LM80-08 and projected values from IESNA TM21-11.

## LED DRIVER

**OUTPUT POWER SUPPLY:** Class II

**POWER FACTOR (P<sub>f</sub>):** >.9

**THD:** <20%

**INPUT VOLTAGE:** 120V at 50/60 Hz

**DIMMING:**

\* TRIAC/ELV, 5% (120V AC Only)

## CONSTRUCTION

**HOUSING:** Formed & Welded All-Aluminum

**FINISH:**

- Powdercoat Paint Colors (4)
  - Black (BK)
  - White (WH)
  - Antique Bronze (AB)
  - Silver Gray (SL)

## INSTALLATION

**SIZE:** 6" Dia. x 12" H x 8¾" E

**MOUNTING:** Surface wall mounting only.

Mounting canopy assembly secures luminaire to wall-mounted junction box.

## COMPLIANCES/WARRANTY

cULus LISTED

FCC COMPLIANT

2-YEAR LIMITED WARRANTY

RoHS COMPLIANT

SUITABLE FOR WET LOCATIONS

ENERGY-EFFICIENT

LED

DOWNLIGHT CYLINDER

Catalog #:

Type:

Project:

Prepared By:

### AT A GLANCE

Fixed-position downlight cylinder incorporating state-of-the-art LED technology. Aperture 6". Offered as a surface wall mount fixture.

## ORDER CONFIGURATOR

To order, select one option from each table column to configure the desired cylinder product catalog code. Then, fill in the boxes below (e.g., Cylinder #: CL603-30-10-LELV-AB-1).

CYLINDER #					
CL603	30	10	LELV		1
CYLINDER MODEL	CCT	LUMENS	DIMMING	FINISH	VOLTAGE
<input checked="" type="checkbox"/> CL603	<input checked="" type="checkbox"/> 30 3000K	<input checked="" type="checkbox"/> 10 1000 lm	<input checked="" type="checkbox"/> LELV Flicker-Free TRIAC/ELV, 5% (120V Only)	<input type="checkbox"/> BK Black (Painted) <input type="checkbox"/> WH White (Painted) <input type="checkbox"/> AB Antique Bronze (Painted) <input type="checkbox"/> SL Silver Gray (Painted)	<input checked="" type="checkbox"/> 1 120V

### QUICK VIEW

