



LIGHT SOURCES

- LED/INCANDESCENT COMPATIBILITY:**
- 2 x 75 Watts Max LED (150W Max Total) (Lamps Sold Separately)
 - 2 x 75 Watts Max Incandescent (150W Max Total) (Lamps Sold Separately)
 - 1 Uplight Medium Base Lampholder & 1 Downlight Medium Base Lampholder
 - 120V Only

DIMMING: Dimmable (Lamp Dependant)

CONSTRUCTION

HOUSING: Formed & Welded All-Aluminum

FINISH:

- Powdercoat Paint Colors (4)
 - Black (BK)
 - White (WH)
 - Antique Bronze (AB)
 - Silver Gray (SL)

INSTALLATION

SIZE: 5" Dia. x 14" H x 7¾" E

MOUNTING: Surface wall mounting only. Mounting canopy assembly secures luminaire to wall-mounted junction box.

COMPLIANCES/WARRANTY

- cULus LISTED
- FCC COMPLIANT
- 5-YEAR LIMITED WARRANTY
- RoHS COMPLIANT
- SUITABLE FOR WET LOCATIONS
- ENERGY-EFFICIENT
- LED COMPATIBLE
- UPLIGHT/DOWNLIGHT CYLINDER



Catalog #:

Type:

Project:

Prepared By:

AT A GLANCE

Fixed-position uplight/downlight cylinder incorporating a medium base socket. Aperture is 5". For use with LED or incandescent lamps.

ORDER CONFIGURATOR

To order, select one option from each table column to configure the desired cylinder product catalog code. Then, fill in the boxes below (e.g., Cylinder #: Ci504-AB-1).

CYLINDER

Ci504		1
-------	--	---

CYLINDER MODEL	FINISH	VOLTAGE
<input checked="" type="checkbox"/> Ci504	<input type="checkbox"/> BK Black (Painted)	<input checked="" type="checkbox"/> 1 120V
	<input type="checkbox"/> WH White (Painted)	
	<input type="checkbox"/> AB Antique Bronze (Painted)	
	<input type="checkbox"/> SL Silver Gray (Painted)	

Surface Wall Mount

