



## LIGHT SOURCES

- LED/INCANDESCENT COMPATIBILITY:**
- 2 x 75 Watts Max LED (150W Max Total) (Lamps Sold Separately)
  - 2 x 75 Watts Max Incandescent (150W Max Total) (Lamps Sold Separately)
  - 1 Uplight Medium Base Lampholder & 1 Downlight Medium Base Lampholder
  - 120V Only

**DIMMING:** Dimmable (Lamp Dependant)

## CONSTRUCTION

**HOUSING:** Formed & Welded All-Aluminum

### FINISH:

- Powdercoat Paint Colors (4)
  - Black (BK)
  - White (WH)
  - Antique Bronze (AB)
  - Silver Gray (SL)

## INSTALLATION

**SIZE:** 6" Dia. x 18" H x 8¾" E

**MOUNTING:** Surface wall mounting only. Mounting canopy assembly secures luminaire to wall-mounted junction box.

## COMPLIANCES/WARRANTY

- cULus LISTED
- FCC COMPLIANT
- 5-YEAR LIMITED WARRANTY
- RoHS COMPLIANT
- SUITABLE FOR WET LOCATIONS
- ENERGY-EFFICIENT
- LED COMPATIBLE
- UPLIGHT/DOWNLIGHT CYLINDER



Catalog #:

Type:

Project:

Prepared By:

### AT A GLANCE

Fixed-position uplight/downlight cylinder incorporating a medium base socket. Aperture is 6". For use with LED or incandescent lamps.

## ORDER CONFIGURATOR

To order, select one option from each table column to configure the desired cylinder product catalog code. Then, fill in the boxes below (e.g., Cylinder #: Ci604-AB-1).

CYLINDER #		
Ci604		1

CYLINDER MODEL	FINISH	VOLTAGE
<input checked="" type="checkbox"/> Ci604	<input type="checkbox"/> BK Black (Painted) <input type="checkbox"/> WH White (Painted) <input type="checkbox"/> AB Antique Bronze (Painted) <input type="checkbox"/> SL Silver Gray (Painted)	<input checked="" type="checkbox"/> 1 120V

### QUICK VIEW

#### Surface Wall Mount

