



CMH LIGHT SOURCE

BI-PIN BASE: G12
TUBULAR CMH LAMP:
 T6 Envelope (Lamps Furnished by Others)
WATTAGE:
 39W MH, 70W MH, 100W MH, or 150W MH
NOT FOR DIMMING APPLICATIONS

ELECTRICAL

INPUT VOLTAGE:
 120V/277V Universal at 50/60 Hz
POWER FACTOR (Pf): >.9
THERMAL MANAGEMENT: Passive
INTEGRAL ELECTRONIC HID BALLAST

OPTICS

BEAM ANGLES: 20°, 30°, or 40°
GIMBAL AIMING: Up to 45° tilt and up to 355° rotation in upper position. 90° horizontal aiming in lowest position.

INSTALLATION

CEILING:

- Accommodates Up to 1¼" Thickness
- Non-Type IC, Insulation to Be Kept 3" Away
- 7¾" x 7¾" Ceiling Cutout Size
- Maintenance Access from Above and Below Ceiling

MOUNTING:

- Integrated Universal Mounting Brackets
 - Advanced High-Strength Steel (AHSS)
- Hanger Bars (Sold Separately) (See Below)

J-BOX WIRING:
 Integral Thru-Branch, 4 In/4 Out

REFLECTOR

ADJUSTABLE, ROTATING GIMBALS:
 Integral to Internal CMH

DESIGN:
 Self-Flanged, Two-Piece Construction

FINISH/COLORS/TRIM:
 Anodized (Clear); Painted White Flange Trim

PRODUCTION PROCESS:
 CNC Precision-Spun

MATERIAL: Specification-Grade Aluminum Alloy, .060" Thick

COMPLIANCES/WARRANTY

cULus LISTED
ENERGY STAR (CONSULT FACTORY)
FCC COMPLIANT
5-YEAR LIMITED WARRANTY
RoHS COMPLIANT
SUITABLE FOR DAMP LOCATIONS
ENERGY-EFFICIENT HID
RECESSED DOWNLIGHT



Catalog #:

Type:

Project:

Prepared By:

AT A GLANCE

Recessed, architectural downlight utilizing a Ceramic Metal Halide lamp on one double gimbal. Ideal for down and accent lighting in indoor spaces where performance and design matter. Gimbal offers multiple lamp/aiming angle options. This luminaire utilizes a T6 CMH lamp with G12 base (lamp not supplied). Select from 39W through 150W per lamp options. Reflector optics packages of 20°, 30°, or 40° are available. Precision-formed all steel housing. Aperture is 6½" x 6½" and flanged with ¾" wide trim. Overall trim dimensions are 8¼" x 8¼".

ORDER CONFIGURATOR

To order, select one option from each table column to configure the desired recessed multiple product catalog code. Then, fill in the boxes below (e.g., Recessed Multiple #: MM661-070-30-BK-1). To order additional items (optional), up to one option from each table column can be selected from the Optional section. Then, fill in the dashed box(es).

RECESSED MULTIPLE

MM661			BK	
RECESSED MULTIPLE MODEL	FIXTURE WATTAGE	OPTICS	INTERIOR FINISH	VOLTAGE
<input checked="" type="checkbox"/> MM661	<input type="checkbox"/> 039 39W MH <input type="checkbox"/> 070 70W MH <input type="checkbox"/> 100 100W MH <input type="checkbox"/> 150 150W MH	<input type="checkbox"/> 20 20° <input type="checkbox"/> 30 30° <input type="checkbox"/> 40 40°	<input checked="" type="checkbox"/> BK Black (Painted)	<input type="checkbox"/> 1 120V <input type="checkbox"/> 2 277V

OPTIONAL

HANGER BARS (SOLD SEPARATELY)
<input type="checkbox"/> HBC C Channel
<input type="checkbox"/> HBF Flat Style
<input type="checkbox"/> HBJ Wood Joist

QUICK VIEW

