

FEATURES       

LED LIGHT ENGINE

WATTS/LUMENS:
40W/5,200 lm or 80W/10,400 lm

CRI/CCT:
80/4000K

BINNING: 3 SDCM

THERMAL MANAGEMENT: Passive

LIFE (RATED): 50,000 hours based on LED testing per LM80-08 and projected values from IESNA TM21-11.

LED DRIVER

OUTPUT POWER SUPPLY: Class II

POWER FACTOR (Pf): ≥0.90

THD: <20%

INPUT VOLTAGE: 120V/277V at 50/60 Hz

DIMMING: Yes (with 0-10V type dimmer)

SURGE PROTECTION:

LN-PG: 5KV, L-N:4KV

OPERATING TEMP.: -30°C to +45°C

OPTICS

BEAM ANGLE: 120°

LENS

DESIGN: One Piece; Fluted

COLOR: Clear

MATERIAL: Polycarbonate

INSTALLATION

MOUNTING:

Surface Mounting

- Three through holes for surface mounting.
- Connection bracket for conduit included.

Pole Mounting

- Fits 1.4"-1.6" (35-40mm) diameter poles.

COMPLIANCES/WARRANTY

 cETLus LISTED

 FCC COMPLIANT

 5-YEAR LIMITED WARRANTY

 COMPLIANT

 IP65; SUITABLE FOR OUTDOORS

 ENERGY-EFFICIENT

 LED

 DOWNLIGHT; 120°

BODY CONSTRUCTION

Die-cast Aluminum with Dark Bronze finish.



Catalog #:

Type:

Project:

Prepared By:

AT A GLANCE

Simple and utilitarian - just like a Barn Light should be!

Features built-in surge protection and a powder coated die-cast aluminum body. Reflector optics of 120°. Fluted optic design reduces glare and allows for smooth light output.


ORDER CONFIGURATOR

To order, select one of two fixture versions from the list below (example #: BL01-40-50-12-BZ-PC).

MODELS

BL01-40-50-12-BZ-PC: 5,200 lumens; 4,000K / 80CRI; 40 watts; 120-277V; 10.8" L x 4.0" H x 7.0" Diameter

BL02-40-90-12-BZ-PC: 10,400 lumens; 4,000K / 80CRI; 80 watts; 120-277V; 14.0" L x 5.0" H x 9.5" Diameter



Note: Photos not to scale.

