

FEATURES    **DRY ONLY**

LED LIGHT ENGINE

DIRECTION: Downward; 90°
LIGHT SOURCE: Lumileds LED 2835
COLOR TEMPERATURE: 4,000K **CRI:** 80
HBU1-40-23-90-BK HBU1-40-36-90-BK
WATTAGE: 150W 240W
LUMENS: 22,500 L 36,000 L

OPTICS

Clear Polycarbonate Lens; 90°

DIMMING

DIMMING: Yes; 0-10V

DIMENSIONS

11.6"W x 8.25"H or 13.8"W x 8.3"H

CONSTRUCTION

FIXTURE MATERIAL: Cast Aluminum

COLORS/FINISHES

FINISH: High quality black painted finish.
ELECTRICAL CORD: Black

INSTALLATION

CEILING MOUNTED:

- 6in. Electrical Cord
- Hook Included
- Optional: Pendant Pipe Adaptor (3/4" MPT)
- Optional: U-Bracket Mount
- Sensor Base & Cap Included
- Suitable for Indoor Use Only

FEATURES

 **SAVES ENERGY BY USING LED**

COMPLIANCES

 **UL LISTED**
 **DRY LOCATIONS ONLY**

WARRANTY

 **5-YEAR LIMITED LED WARRANTY**

ELECTRICAL

- Universal Voltage (120V-277V, 50/60Hz.)
- Wattage: 150W or 240W
- OPTIONAL:**
- 347-480V, 50/60Hz Driver
- Dimming/On-Off Motion Sensor (# MC054)



Catalog #:

Type:

Project:

Prepared By:

AT A GLANCE

Full featured LED Highbay ceiling fixture. Durable high-quality cast aluminum exterior with black powder coated finish. The fixture is dimmable with 0-10V type dimmers or can be controlled by the optional dimming/on-off motion sensor.



150 watt (HBU1-40-23-90-BK)



240 watt (HBU1-40-36-90-BK)

ORDER CONFIGURATOR

The highbay product catalog code is pre-filled for your convenience below (e.g., highbay# HBU1-40-23-90-BK).

HIGHBAY #				OPTIONAL		
HBU1	40		90 - BK	<input type="checkbox"/> - (+J) 347-480VAC, 50/60HZ)	<input type="checkbox"/> - MC054 Dimming/On-Off Motion Sensor Module)	<input type="checkbox"/> - Mounting Bracket
MODEL	COLOR TEMPERATURE	LUMENS	OPTICS & COLOR	<input type="checkbox"/> - Pipe Adaptor (accepts 3/4" MPT)		
<input checked="" type="checkbox"/> 2124	<input checked="" type="checkbox"/> 40 (4,000k)	<input type="checkbox"/> - 23 (22,500 L) <input type="checkbox"/> - 36 (36,000 L)	<input checked="" type="checkbox"/> - 90 (90°) <input checked="" type="checkbox"/> - BK (black)			

