

FEATURES     

### LED LIGHT ENGINE

**WATTS/LUMENS:**  
14W / 850 lm

**CRI/CCT:**  
90 / 3000K

**THERMAL MANAGEMENT:** Passive

**LIFE (RATED):** 50,000 hours based on LED testing per LM80-08 and projected values from IESNA TM21-11.

### INSTALLATION

**CEILING or WALL:**

- Surface Mounted
- Ceiling or Wall
- Indoors Only

**MOUNTING:**

- J-Box mounted

### DIMENSIONS

8" Diameter x 1" High

### OPTICS

Frosted plastic lens.

### ENCLOSURE COLORS

White, Brushed Nickel, or Antique Bronze (i.e. almost black grey-brown)







### LED DRIVER

**OUTPUT POWER SUPPLY:**  
AC LED Engine

**INPUT VOLTAGE:**  
120V at 50/60 Hz

**DIMMING:**  
No

### COMPLIANCES/WARRANTY

-  cETLus LISTED
-  ENERGY STAR (CONSULT FACTORY)
-  FCC COMPLIANT
-  5-YEAR LIMITED WARRANTY
-  ENERGY-EFFICIENT
-  LED



Catalog #:

Type:

Project:

Prepared By:

### AT A GLANCE

8" diameter, low-profile, ceiling mounted LED luminaire. Cast aluminum body and trim with frosted lens.

## ORDER CONFIGURATOR

To order, select one option from each table column to configure the desired product catalog code. Then, fill in the boxes below.

### RECESSED DOWNLIGHT #

7052 -

MODEL	FRAME COLOR				
<input checked="" type="checkbox"/> 7052	<input type="checkbox"/> -6 White				
	<input type="checkbox"/> -33 Brushed Nickel				
	<input type="checkbox"/> -79 Antique Bronze				

QUICK VIEW

