

FEATURES     

LED LIGHT ENGINE

WATTS/LUMENS:

22W / 1320 lm

CRI/CCT:

90 / 3000K

THERMAL MANAGEMENT: Passive

LIFE (RATED): 50,000 hours based on LED testing per LM80-08 and projected values from IESNA TM21-11.

INSTALLATION

CEILING or WALL:

- Surface Mounted
- Ceiling or Wall
- Indoors Only

MOUNTING:

- J-Box mounted

DIMENSIONS

12" Diameter x 1" High

OPTICS

Frosted plastic lens.

ENCLOSURE COLORS

White, Brushed Nickel, or Antique Bronze (i.e. almost black grey-brown)

LED DRIVER

OUTPUT POWER SUPPLY:

AC LED Engine







INPUT VOLTAGE:

120V at 50/60 Hz

DIMMING:

No

COMPLIANCES/WARRANTY

-  **cETLus LISTED**
-  **ENERGY STAR (CONSULT FACTORY)**
-  **FCC COMPLIANT**
-  **5-YEAR LIMITED WARRANTY**
-  **ENERGY-EFFICIENT**
-  **LED**



Catalog #:

Type:

Project:

Prepared By:

AT A GLANCE

12" diameter, low-profile, ceiling mounted LED luminaire. Cast aluminum body and trim with frosted lens.

ORDER CONFIGURATOR

To order, select one option from each table column to configure the desired product catalog code. Then, fill in the boxes below.

RECESSED DOWNLIGHT

7054 -

MODEL	FRAME COLOR				
<input checked="" type="checkbox"/> 7054	<input type="checkbox"/> -6 White				
	<input type="checkbox"/> -33 Brushed Nickel				
	<input type="checkbox"/> -79 Antique Bronze				

QUICK VIEW

