


FEATURES      

LED LIGHT ENGINE

WATTS/LUMENS: 15W/800 lm
CRI/CCT: 80/3000K
POWER FACTOR (Pf): >.95
THD: <20%
INPUT VOLTAGE: 120V at 50/60 Hz
STARTING TEMPERATURE: ↓ -20°C
DIMMING:  10% of Output
EDISON ADAPTER:
 Medium Base (E26) with Connector
 (Compatible with Incandescent Downlights)
TWIST AND LOCK BI-PIN BASE:
 GU24 with Connector (Compatible with
 Compact Fluorescent Downlights)
LENS COVER: Sealed and Frosted
MATERIAL:
 All Die-Cast Aluminum Construction
FINISH: Powder-Coat Polyester (Painted)

INSTALLATION

CEILING:



- Accommodates Up to 1¼" Thickness
- Type IC or Non-Type IC
 - Type IC Suitable for Direct Contact with Insulation
 - Non-Type IC Insulation to Be Kept 3" Away

MOUNTING:

- Dual-Torsion Spring Mounting Assemblies
- Integral Mounting Springs

SUITABLE FOR INDOOR OR OUTDOOR USE

COMPLIANCES/WARRANTY

 **cULus LISTED**
 **ENERGY STAR (CONSULT FACTORY)**
 **FCC COMPLIANT**
 **5-YEAR LIMITED WARRANTY**
 **RoHS COMPLIANT**
 **SUITABLE FOR WET LOCATIONS**
 **LED**
 **RECESSED DOWNLIGHT**

TRIMS



Catalog #:
 Type:
 Project:
 Prepared By:

AT A GLANCE
 Recessed, fixed-position LED retrofit downlight, with assorted trim options, for applications utilizing standard plenum heights. Turn incandescent or compact fluorescent recessed downlights into LEDs using E26 medium base adapters or GU24 base lampholders. Installs onto most commercial 6" aperture recessed downlight housings. All die-cast aluminum construction prevents corrosion and increases lamp life. Accommodates non-type IC and type IC. Sealed and frosted lens cover. Suitable for wet locations. Starting temperature -20°C. Dimmable.

ORDER CONFIGURATOR

To order, select one option from each table column to configure the desired retrofit downlight product catalog code. Then, fill in the boxes below (e.g., Retrofit Downlight #: RL6R-SA-G).

RETROFIT DOWNLIGHT

RETROFIT DOWNLIGHT MODEL	TRIM	BASE
<input checked="" type="checkbox"/> RL6R	<input type="checkbox"/> CW Clear Reflector, Round White Flange <input type="checkbox"/> GR Ornamental Glass, Round White Flange <input type="checkbox"/> GS Ornamental Glass, Square White Flange <input type="checkbox"/> RA Adjustable Gimbal, Round White Flange <input type="checkbox"/> SA Adjustable Gimbal, Square White Flange <input type="checkbox"/> WW White Reflector, Round White Flange	<input type="checkbox"/> E E26 Medium Base with Connector <input type="checkbox"/> G GU24 Base with Connector

QUICK VIEW

