

LED LIGHT ENGINE

WATTS/LUMENS: 10W/750 lm
CRI/CCT: 80/3000K
BINNING: 3 SDCM
THERMAL MANAGEMENT: Passive
LIFE (RATED):
 50,000 hours based on LED testing per LM80-08 and projected values from IESNA TM21-11.

OPTICS

BEAM ANGLES: 36°
ADJUSTABLE/HORIZONTAL AIMING: Up to 90° tilt from vertical axis and up to 355° rotation around vertical axis.
DESIGN: Unique Integral Construction
FINISH/COLORS: Anodized (Clear)
MATERIAL: Specification-Grade Aluminum Alloy

CONSTRUCTION

CYLINDER MATERIAL: Die-Cast Aluminum
FINISH/COLORS:

- Powdercoat Paint Colors
 - White (WH)
- Plated Finish
 - Brushed Nickel (BN)

INSTALLATION

MOUNTING:

- Mounts to 120V AC *QuantaLight* Track Systems
 - TSQ1: 1-Circuit/1-Neutral (1C1N)
 - TSQ2: 2-Circuit/1-Neutral (2C1N)
- Mounts to 1-Circuit or 2-Circuit Track System Platforms

ADAPTERS: Listed Components

LED DRIVER

OUTPUT POWER SUPPLY: Class II
POWER FACTOR (Pf): >.9
THD: <20%
INPUT VOLTAGE: 120V at 50/60 Hz (System Adapter Dependant)
DIMMING: TRIAC/ELV 5% dimmable on the input primary, line-side circuit of the track system. Consult dimmer manufacturer for compatibility and conditions of use.

COMPLIANCES/WARRANTY

- Ⓢ cETLus LISTED
- FC FCC COMPLIANT
- 5-YEAR LIMITED WARRANTY
- RoHS COMPLIANT
- ENERGY-EFFICIENT
- LED
- DRY ONLY DRY LOCATIONS ONLY

TRACK HEAD MODEL	<input checked="" type="checkbox"/> TL127
TRACK ADAPTER	<input checked="" type="checkbox"/> Q2 1C1N & 2C1N (120V)
CCT	<input checked="" type="checkbox"/> 30 3000K
LUMENS	<input checked="" type="checkbox"/> 08 750 lm
OPTICS	<input checked="" type="checkbox"/> 36 36°
FINISH	<input type="checkbox"/> 6 White (Painted) <input type="checkbox"/> 33 Brushed Nickel

TL127
LED TRACK HEADS



Product feature icons: Dry Only, LED, Integral LED, 355° rotation, 90° tilt, 5 Year warranty, 1C1N, 2C1N, and certification logos (ETL, RoHS, FC, V-GHS).

QUICK VIEW

